

SF-IPT943HG-2E

2 MP IP Turret Camera
1/2.8" Progressive Scan CMOS
Compression H.265
2.8 mm Lens
IR Range 30m
IP67



Safire
IP camera
ECO Range
1/2.8" Progressive Scan CMOS
2 Megapixel (1920x1080)
2.8 mm Lens
DWDR
Compression H.265 / H.264
IR Cut
0 Lux
IR Range 30 m
RJ-45 10/100 BaseT
PoE IEEE802.3af
Weatherproof IP67
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	SAFIRE
Range	ECO
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Minimum illumination	0.01 Lux / F1.2
Infrared lighting	0 Lux / Matrix LED IR (30 m)
Lens	2.8 mm (H: 114.8°)
Compression	H.265 / H.264 / MJPEG
Video Bit Rate	32 Kbps – 8 Mbps
Main Stream rate	1080p / 720p (1 – 25 FPS)
Sub Stream Rate	640x480 / 640x360 / 320x240 (1 – 25 FPS)
Third Stream Rate	640x480 / 640x360 / 352x288 (1 – 25 FPS)
Image improvements	DWDR, BLC, 3D-DNR, MD, AGC, Privacy Mask, ROI
Day / Night	Auto / Programmable / Colour / BW (Black and White)
Internal memory	No
Network interface	Ethernet 10/100M BaseT
Alarms	No
Audio	No
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI, ISAPI
Lens Adjustment	3 axis
Power	DC 12 V / 500 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67
Material	Body: Metal / Base: Plastic
Temp. operation	-30° C ~ +60° C
Dimensions	93.2 mm (H) x 110 (Ø) mm
Base dimensions	85 (Ø) mm / 3 screws
Weight	360 g