

SF-IPB025CWA-4U-AI2

4 MP IP Camera
1/2.7" Ultra Night color
Compression H.265+ / H.265
2.8mm / WDR Lens
Truesense2: Improved false alarm
filter



Safire
IP Bullet Camera
Ultra Range
4 Megapixel Progressive Scan CMOS Night Color
Error en DeepL Request failed with status code 503
0 Lux
2.8 mm Lens
WDR
3D DNR
Compression H.265+/H.264+
White light range 40 m
TrueSense2, improved false alarm filter for vehicles and people
Face Capture: Compatible with facial recognition recorders
Line crossing detection, intrusion detection, region entry detection, region exit detection, etc
Movement detection 2.0 (human and vehicle target classification)
Integrated microphone
RJ-45 10/100 BaseT
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible
Micro SD card recording
PoE IEEE802.3af
Weatherproof IP67

Specifications

Brand	SAFIRE
Image sensor	1/1.8" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2688 x 1520)
Minimum illumination	0.0005 Lux / F1.0 WL
Lighting	0 Lux / White light range 40 m
Lens	2.8 mm (H: 112°, V: 61°)
Bitrate	32 Kbps – 8 Mbps
Main Stream rate	4Mpx / 3Mpx / 1080p / 720p (1 – 25 FPS)
Extra Stream rate	640x480, 640x360 (1 – 25 FPS)
Compression	H.265/H.264/H.265+/H.264+
Image improvements	WDR (130dB), BLC, 3D-DNR, HLC
Advanced features	Line-crossing detection intrusion entry / exit area
Truesense 2	Motion Detection, Line Crossing, Entry / Exit area Truesense, Face capture
Face Capture	YES (Compatible with Safire's Face Recognition recorders)
Internal memory	MicroSD card, Max 256 GB
Network interface	Ethernet 10/100 BaseT
Alarms	No
Audio	Built-in microphone
Remote access	NVR, Web Browser, App Smartphone and PC Software Safire Control Center
Interoperability	ONVIF
Power	DC 12V / 0.5A, max. 6W, PoE IEEE802.3af max. 7.5W
Degree of protection	IP67
Temp. operation	-30° C ~ +60° C
Dimensions	215.2 mm (H) x 78.8 (Ø) mm
Base dimensions	85.3 (Ø) mm (3 screws)
Weight	695 g