

SF-IPT833WA-8P-HV

8 MP IP Camera

1/2.8" Progressive Scan CMOS

Motion Detection 2.0 of humans and vehicles

Lens 2.8 mm / IR LEDs Range 30 m

Compression H.265+, H.265, H.264+, H.264

Built-in microphone



Safire

IP camera

PRO Range

1/2.8" Progressive Scan CMOS

8 Megapixel (3840×2160)

2.8 mm Lens

0 Lux

IR Range 30 m

Human and vehicle motion detection with Motion Detection 2.0

Facial Recognition

Compression H.265+/H.265/H.264+/H.264

WDR

RJ-45 10/100 BaseT

Built-in microphone

Weatherproof IP67

IR Cut

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Specifications

Brand	SAFIRE
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	8 Megapixel (3840x2160)
Main Stream rate	20 fps (3840×2160) 25 fps (3200×1800, 2688×1520, 1920×1080, 1280×720) [%VAR%]
Sub Stream Rate	25 fps (640×480, 640×360)
Third Stream Rate	25 fps (1920×1080, 1280×720, 640×480, 640×360) [%VAR%]
Compression	H.265+, H.265, H.264+, H.264
Bitrate	32 Kbps ~ 16 Mbps
Lens	2.8 mm (H: 103°, V: 55°)
Minimum illumination	0.005 Lux (colour) / 0 Lux (B/N)
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	WDR (120 dB), BLC, 3D-DNR, AWB, ROI, Motion detection, Mirror
Day / Night	Removable mechanical ICR filter
Motion Detection 2.0	Advanced motion detection of humans and vehicles on the scene
Intelligent functions	Line Crossing, Area Intrusion, Face Detection
Audio	Integrated microphone
Network interface	Ethernet 10/100 BaseT
Storage	MicroSD card slot up to 256GB, NAS
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	12 VDC / 500 mA (MAX 7.5W), PoE 802.3af
Degree of protection	Weatherproof IP67
Temp. Functioning	-30° C ~ +60° C
Dimensions	Ø127.3 × 95.9 mm
Weight	600 g