

SF-NVR6104-4KE-4P

NVR for IP cameras

4 CH video PoE+ 50W / Compression

H.265+

Maximum resolution 8.0 Mpx

Bandwidth 40 Mbps

Outputs 4K HDMI & VGA

Supports 1 hard disk



Safire

NVR for IP cameras

4 CH

40 Mbps bandwidth supported

Maximum resolution 8 Megapixel (4096x2160)

Compression H.265+/H.265/H.264+/H.264

VGA and HDMI 4K output

IP Dual Stream Access

Mouse

Space for 1 HDD

4 PoE ports IEEE802.3af/at

WEB, CMS and Smartphone interface

ONVIF Compatible

Specifications

Brand	Safire
Inputs for IP cameras	LAN port up to 4 PoE channels
Power over Ethernet	4 (Max. 50W)
IP compatible cameras	SAFIRE (native protocol), ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	H.265+ / H.265 / H.264+ / H.264
Display resolution	3840x2160, 2560x1440, 1920x1080, 1280x1024, 1280x720, 1024x768
Total bandwidth	40 Mbps downstream / 80 Mbps upstream
Main Stream recording	8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	No
Recording method	Manual, programmed, motion detection
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	1 x USB 2.0 (front) / 1 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Safire Control Center Smartphone App and PC Software
Power	DC 48V / 1.35A
Dimensions / Weight	48 (H) x 320 (W) x 240 (D) mm / 0.9 Kg